

## EUROLITE LED TMH-W555 Moving Head Wash Zoom

Washlight with 37 bright 15 W RGBW LEDs, zoom, macros, patterns and color temperature setting

Art. No.: 51785920

GTIN: 4026397693706



### Features:

- 37 LEDs 15 W 4in1 RGBW (homogenous color mix) <BR> segments controlled separately
- Positioning within 540° PAN, 205° TILT
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Dimmer electronic; color blend stepless; patterns animated; pulse effect adjustable; color animations with two adjustable colors; program selection
- Strobe effect
- The device is cooled by temperature-controlled fan at the head; cooling fan at the base
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- Variable color temperature 2500 K - 10000 K
- Multicolor LCD display
- Mains input and output for power linking up to 4 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; rental
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397693706

Weight: 15,80 kg

Length: 0.47 m

Width: 0.36 m

Height: 0.47 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 490 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 4 A fuse replaceable
Lamp type:	LED lamp
LED type:	37 x 15 W 4in1 RGBW (homogenous color mix)
Max. TILT movement:	205° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1 - 21 Hz
Equipment:	Zoom motor driven
DMX channels:	24; 36; 48
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the head Cooling fan at the base
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle (1/2 peak):	1 - 20°
Beam angle (1/10 peak):	8 - 38°
Color temperature:	2500K - 10000K adjustable
Illuminance in Lux (lx):	Narrow red (R) 1m: 14703 lx, 3m: 6338 lx, 6m: 1581 lx Narrow green (G) 1m: 36582 lx, 3m: 14313 lx, 6m: 3581 lx Narrow blue (B) 1m: 4622 lx, 3m: 2444 lx, 6m: 666 lx Narrow cold white (CW) 1m: 47065 lx, 3m: 15572 lx, 6m: 3872 lx Narrow all 3m: 35914 lx, 6m: 9025 lx Wide red (R) 1m: 4769 lx, 3m: 624 lx, 6m: 165 lx Wide green (G) 1m: 10949 lx, 3m: 1431 lx, 6m: 386 lx Wide blue (B) 1m: 2021 lx, 3m: 274 lx, 6m: 77 lx Wide cold white (CW) 1m: 11357 lx, 3m: 1505 lx, 6m: 397 lx Wide all 1m: 27092 lx, 3m: 3575 lx, 6m: 956 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 39.0 cm Depth: 26.5 cm Height: 47.5 cm
Weight:	14.30 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

---

**Scope of delivery:**

---

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket