

EUROLITE LED IP TMH-W285 Hypno Moving Head Wash

Weather-proof moving washlight with RGBW LEDs, backlighting via RGB hypno LEDs and zoom

Art. No.: 51785932

GTIN: 4026397753639



Description:

Weatherproof moving heads do not have to be super expensive; this model proves exactly that. It can withstand heavy rain while combining solid quality with an attractive price.

Equipped with 19 main LEDs featuring RGBA color mixing and an additional LED ring, the fixture offers a wide range of effect possibilities. The LED ring provides extra color accents and can also display animations.

The motorized zoom allows the beam angle to be adjusted from 2° to 48°, making it an ideal choice for open-air parties, concerts, and fairground applications.

Logistic

EAN / GTIN: 4026397753639

Weight: 17,10 kg

Length: 0.56 m

Width: 0.38 m

Height: 0.48 m

Features:

- 19 LEDs 15 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
3 segments controlled separately
- 72 LEDs 0.12 W SMD 2528 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 260° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Dimmer; Dimmer speed (step response) adjustable; color blend stepless; color macros; colors preset
- Wash effect; beam effect
- The device is cooled by cooling fan at the head
- Control via stand-alone; DMX; RDM; master/slave function
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 2° - 48°
- With omega bracket

- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 4 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; rental; restaurants, bars and hotels; theater
- Application possibility: Standing; suspended
- Fixtures available for Light Captain

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	195 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	19 x 15 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 72 x 0.12 W SMD 2528 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	260° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1.3 - 10.6 Hz
Equipment:	Zoom motor driven
DMX channels:	18; 26
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 1 x 5-pin XLR (F) mounting version IP
Cooling:	1 x cooling fan at the head
Control:	Stand-alone; DMX; RDM; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	26000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	2° - 48°
Beam angle (1/2 peak):	2 - 30°
Beam angle (1/10 peak):	8 - 48°
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	Multicolor LCD display

Status LED:	DMX, fault
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø11mm
Use of brands:	Built with SEETRONIC connector
Material:	Plastic
Dimensions:	Width: 38.8 cm Depth: 25.7 cm Height: 49.1 cm
Weight:	15.40 kg
Noise classification:	Class 2 (slight noise) depending on mode used
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket