

EUROLITE LED TMH Bar H240 Moving Head Beam/Flower

LED lighting system with 4 individually controllable 60 W moving heads with flower effect in RGBW

Art. No.: 51786057

GTIN: 4026397755497



Description:

This bar combines four fully featured moving heads in a single system. Each unit is equipped with four 15 W LEDs with RGBW color mixing, allowing for both tight beams and room-filling flower effects.

The bar can be used flexibly: mounted on a stand, placed on the floor, or suspended from a truss. Special attention has been paid to ease of control, ensuring that even smaller DMX controllers can operate the bar efficiently. Dedicated modes are available that allow a wide range of positions, movements, chases, and effects to be created using only a few DMX channels. A great example of a suitable controller is the Eurolite Color Chief, which pairs perfectly with this bar.

Features:

- 16 LEDs 15 W SMD 6065 4in1 QCL RGBW
4 moving lights effects controlled separately
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Lens rotation
- Dimmer electronic; Motion macros adjustable; color selection; color macros adjustable
- Flower effect; beam effect
- 22 integrated show programs
- The device is cooled by cooling fan at the base; cooling fan at the head
- Control via stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 2°

Logistic

EAN / GTIN: 4026397755497

Weight: 14,25 kg

Length: 1.08 m

Width: 0.32 m

Height: 0.22 m

- With omega bracket
- Monochrome 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; stage; mobile djs / entertainer; restaurants, bars and hotels; party room
- Application possibility: Standing; suspended
- Fixtures available for Light´J; Light Captain; Colorchief

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	16 x 15 W SMD 6065 4in1 QCL RGBW
Max. TILT movement:	180° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	2 - 15 Hz
Equipment:	Lens rotation
DMX channels:	5; 9; 14; 16; 25; 29; 44; 52
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x cooling fan at the base 4 x cooling fan at the head
Control:	Stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	11000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	2°
Beam angle (1/2 peak):	2
Beam angle (1/10 peak):	6
Lamp life:	20000 h
Housing color:	Black
Attachment system:	Tube: Ø 35mm 2x omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Control elements:	Power switch
USB port:	Type A

Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø10mm
Material:	Metal
Dimensions:	Width: 100 cm Depth: 17.5 cm Height: 26.0 cm
Weight:	12.70 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 2 x safety eyelet