

## EUROLITE LED TCL-150 Color Changer COB

LED color changer with 30 W LED, gobo and color wheel

Art. No.: 51786110

GTIN: 4026397687149



### Features:

- Compact design
- Beam reducer gobos make it perfect for illuminating mirror balls
- 1 LED 30 W COB (chip-on-board) cold white (CW)
- Color wheel; gobo wheel with static gobos; focus manual
- Dimmer electronic
- Gobo effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 4 gobos, 3 color dichros and open<BR>shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 12°
- With mounting bracket
- LCD display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397687149

Weight: 2,42 kg

Length: 0.24 m

Width: 0.23 m

Height: 0.21 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	45 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) cold white (CW)
Flash rate:	2 - 28 Hz
Equipment:	Color wheel; gobo wheel with static gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 4 gobos, 3 color dichros and open Shake effect
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; Light J; Colorchief
Projection:	Flicker-free
PWM frequency:	5500 Hz
Beam angle (1/2 peak):	12°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 17.5 cm Width: 16.0 cm Height: 21.5 cm
Weight:	2.12 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### Scope of delivery:

1 x light effect  
1 x user manual  
1 x power cord  
1 x mounting bracket  
2 x screw