

EUROLITE LED TCL-450 Color Changer COB

LED color changer with 90 W LED, gobo and color wheel

Art. No.: 51786114

GTIN: 4026397750645



List price: 296.31 €

incl. 19% VAT.

Description:

Mirror balls look best when illuminated with a highly focused beam of light. The Eurolite TCL-450 is ideal for this purpose: The TCL-450 is equipped with a powerful white light source that produces a sharply defined, focused white beam. Various color filters are available for color effects, and they can also be locked into intermediate positions.

The beam angle can also be optimally adjusted to the size of the mirror ball using various reducing gobos.

Logistic

EAN / GTIN: 4026397750645

Weight: 2,70 kg

Length: 0.24 m

Width: 0.24 m

Height: 0.21 m

Features:

- Compact design
- Beam reducer gobos make it perfect for illuminating mirror balls
- 1 LED 90 W COB (chip-on-board) cold white (CW)
- Focus manual
- Color change; Dimmer electronic
- Gobo effect
- Color wheel with 7 dichroic filters plus open
half colors selectable; rainbow effect with adjustable speed
- Gobo wheel with static gobos, 4 gobos, 3 color dichros and open
shake effect
- 5 integrated show programs
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 11°
- With mounting bracket

- Monochrome LCD display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05VV-F
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 90 W COB (chip-on-board) cold white (CW)
Flash rate:	2 - 29 Hz
Equipment:	Focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable; rainbow effect with adjustable speed
Gobos:	Gobo wheel with static gobos, 4 gobos, 3 color dichros and open Shake effect
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	DMX; sound to light via microphone; master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	5500 Hz
DMX fail mode:	Hold; blackout; auto; sound
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	11°
Lamp life:	20000 h
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
USB port:	1 x type A
Diameter mounting holes:	1 x Ø10mm
Material:	Steel
Dimensions:	Length: 17.5 cm

Width: 16.0 cm
Height: 21.0 cm

Weight:	2.48 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord
1 x mounting bracket