

## EUROLITE LED TSL-1500 Scan

Scanner with 150 W LED, rotating gobos and 4-facet prism, color wheel and motorized focus

Art. No.: 51786127

GTIN: 4026397714456



**List price: 712.81 €**

incl. 19% VAT.

### Features:

- 1 powerful LED 150 W COB (chip-on-board) cold white (CW)
- Positioning within 180° PAN, 70° TILT
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating
- Dimmer electronic
- Gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- 9 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain
- Flicker-free
- With a beam angle of 11°
- OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended; on stand

### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x safety eyelet

### Logistic

EAN / GTIN: 4026397714456

Weight: 8,20 kg

Length: 0.60 m

Width: 0.30 m

Height: 0.25 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	175 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, F 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 150 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	70° positioning
Max. PAN movement:	180°
Flash rate:	0,5 - 21 Hz
Equipment:	Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 4-fold rotating
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 19,8mm Image diameter 17mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	13
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Color temperature:	10000K
Illuminance in Lux (lx):	Cold white (CW) 3m: 15649 lx, 6m: 4147 lx
Housing color:	Black
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Width: 33,5 cm Depth: 16,5 cm Height: 47 cm

Weight:	7,05 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting