

EUROLITE TMH XB-280 Moving Head Beam

Bright, narrow beam with OSD 10 280W discharge lamp, color wheel, gobos and prisms

Art. No.: 51786825

GTIN: 4026397677171



List price: 1010.31 €

incl. 19% VAT.

Features:

- Equipped with an OSD 10 Reflector 280W discharge lamp
- Positioning within 540° PAN, 270° TILT
- Exact positioning (16 bit resolution)
- Color wheel; focus motor-driven; gobo wheel with static gobos; frost filter; prism 8-fold rotating; prism 24-fold rotating
- Dimmer electronic
- Strobe effect
- Color wheel with 14 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open shake effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 2°
- Multicolor LCD display
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397677171

Weight: 16,35 kg

Length: 0.60 m

Width: 0.42 m

Height: 0.30 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	385 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	T 5 A fuse replaceable
Lamp type:	Discharge lamp
Max. TILT movement:	270° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1 - 18 Hz
Equipment:	Color wheel; focus motor-driven; gobo wheel with static gobos; frost filter; prism 8-fold rotating; prism 24-fold rotating
Color generation:	Color wheel with 14 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 13 gobos und open Shake effect
DMX channels:	16; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle:	2°
Beam angle (1/2 peak):	2°
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30,0 cm Depth: 20,5 cm Height: 50,5 cm
Weight:	14,80 kg
Noise classification:	Class 4 (loud noises)