

FUTURELIGHT EYE-19 HCL Zoom LED Moving Head Wash

PRO washlight with 6in1 COB LEDs, color rendering index (CRI) >90 and very large zoom range

Art. No.: 51841313

GTIN: 4026397659658



Features:

- Compact design
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 19 LEDs 17 W high-power 6in1 RGBALC (homogenous color mix)
2 segments controlled separately
- Positioning within 630° PAN, 265° TILT
- Auto position correction (feedback)
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Pulse-width modulation variable; color selection; color blend stepless
- Strobe effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; RDM; master/slave function; sound to light via microphone; W-DMX by wireless solution upgradeable
- Flicker-free
- With a beam angle of 2° - 36°
- Very high color rendering index (CRI)
- Mains input and output for power linking up to 8 units
- For application areas such as: Theater; clubs/dancing school; Trade fair and shop fitting; installation; stage; concerts/FoH's; rental
- Very quiet working noise

Logistic

EAN / GTIN: 4026397659658

Weight: 16,15 kg

Length: 0.52 m

Width: 0.42 m

Height: 0.33 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 300 W |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 19 x 17 W high-power 6in1 RGBALC (homogenous color mix) |
| Max. TILT movement: | 265° positioning auto position correction (feedback) |
| Max. PAN movement: | 630° auto position correction (feedback) |
| Flash rate: | 1 - 18 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 16; 19; 20; 33 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | DMX; RDM; master/slave function; sound to light via microphone; W-DMX by wireless solution upgradeable |
| Fixtures available for: | Light J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 2° - 36° |
| Beam angle (1/2 peak): | 2 - 15° |
| Beam angle (1/10 peak): | 7 - 36° |
| Color rendering index (CRI): | 90 Ra |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 2300 lx, 6m: 617 lx Narrow green (G) 3m: 5241 lx, 6m: 1329 lx Narrow blue (B) 3m: 1118 lx, 6m: 285 lx Narrow amber (A) 3m: 10211 lx, 6m: 2665 lx Narrow lime 3m: 16696 lx, 6m: 4389 lx Narrow cyan 3m: 2453 lx, 6m: 652 lx Narrow all 3m: 34599 lx, 6m: 9025 lx Wide red (R) 3m: 201 lx, 6m: 57 lx Wide green (G) 3m: 469 lx, 6m: 132 lx Wide blue (B) 3m: 105 lx, 6m: 30 lx Wide amber (A) 3m: 877 lx, 6m: 245 lx Wide lime 3m: 1384 lx, 6m: 387 lx Wide cyan 3m: 228 lx, 6m: 64 lx Wide all 3m: 2969 lx, 6m: 827 lx |
| Housing color: | Black |
| Dimensions: | Width: 25.0 cm Depth: 34.2 cm Height: 45.8 cm |

| | |
|-----------------------|--|
| Weight: | 14.40 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 1 x XLR cable
- 1 x declaration of conformity