

## FUTURELIGHT EYE-37 RGBW Zoom LED Moving Head Wash

PRO washlight with RGBW color mixing, very large zoom range and Art-Net

Art. No.: 51841314

GTIN: 4026397629507



### Features:

- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 37 LEDs 10 W high-power 4in1 RGBW (homogenous color mix) LEDs controlled separately
- Positioning within 540° PAN, 265° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Dimmer electronic; color blend stepless; colors preset
- Strobe effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; Art-Net; stand-alone; sound to light via microphone; master/slave function; W-DMX by wireless solution upgradeable
- Flicker-free
- Mains input and output for power linking up to 8 units

### Logistic

EAN / GTIN: 4026397629507

Weight: 22,25 kg

Length: 0.71 m

Width: 0.51 m

Height: 0.34 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 530 W

Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	37 x 10 W high-power 4in1 RGBW (homogenous color mix)
Max. TILT movement:	265° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 30 Hz
Equipment:	Zoom motor driven
DMX channels:	18; 19; 20; 41; 170
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; Art-Net; stand-alone; sound to light via microphone; master/slave function; W-DMX by wireless solution upgradeable
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	2 - 28°
Beam angle (1/10 peak):	8 - 50°
Illuminance in Lux (lx):	Narrow red (R) 3m: 5874 lx, 6m: 1655 lx Wide red (R) 3m: 564 lx, 6m: 146 lx Narrow green (G) 3m: 11065 lx, 6m: 3219 lx Wide green (G) 3m: 1160 lx, 6m: 305 lx Narrow blue (B) 3m: 1666 lx, 6m: 563 lx Wide blue (B) 3m: 202 lx, 6m: 54 lx Narrow cold white (CW) 3m: 15461 lx, 6m: 4527 lx Wide cold white (CW) 3m: 1545 lx, 6m: 408 lx Narrow all 3m: 31814 lx, 6m: 9366 lx Wide all 3m: 3266 lx, 6m: 859 lx
Housing color:	Black
Dimensions:	Width: 44.4 cm Depth: 25 cm Height: 57 cm
Weight:	19.00 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

1 x moving light  
1 x user manual  
1 x power cord  
1 x XLR cable  
1 x declaration of conformity  
1 x mounting bracket