

FUTURELIGHT DMB-50 LED Moving-Head

PRO beam moving head with a 50 W LED and very good RGB color mixing

Art. No.: 51841802

GTIN: 4026397628791



The article is no longer in our assortment.

Features:

- 50W RGB LED engine enables extraordinary projection possibilities
- Even color mixing, sharp, narrow beams, vivid single colors and homogeneous white
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- 1 powerful LED 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 270° TILT
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
- Dimmer electronic; color selection
- Gobo effect; strobe effect
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone; W-DMX by wireless solution upgradeable
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 2°
- Built with NEUTRIK connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397628791

Weight: 14,20 kg

Length: 0.52 m

Width: 0.38 m

Height: 0.29 m

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 115 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 1 x 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| Max. TILT movement: | 270° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven |
| Gobos: | Gobo wheel with static gobos, 17 gobos and open Shake effect |
| DMX channels: | 16; 18; 20; 21 |
| DMX input: | 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; sound to light via microphone; W-DMX by wireless solution upgradeable |
| Preprogrammed in: | Light J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 2° |
| Beam angle (1/2 peak): | 2° |
| Illuminance in Lux (lx): | Red (R) 6m: 4153 lx Green (G) 6m: 28365 lx Blue (B) 6m: 1725 lx All 6m: 34232 lx |
| Housing color: | Black |
| Use of brands: | Built with NEUTRIK connector |
| Dimensions: | Width: 29,8 cm Depth: 26,7 cm Height: 39,8 cm |
| Weight: | 12,40 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |