

EUROLITE Stage Panel 16 HCL LED

Light effect bar with RGBAW+UV color mixing, with 5-pin QuickDMX connector

Art. No.: 51913891

GTIN: 4026397622522



Features:

- 4 segments for dynamic running lights
- 4 barn doors to avoid blinding the audience and for protection during transport
- 16 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 26 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Flicker-free
- With a beam angle of 23°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397622522

Weight: 5,80 kg

Length: 0.56 m

Width: 0.16 m

Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 70 W

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	16 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0.25 - 16 Hz
DMX channels:	2; 3; 5; 6; 8; 11; 24; 32
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	4700 Hz
Beam angle (1/2 peak):	23°
Beam angle (1/10 peak):	42°
Wavelength:	Ultra violet (UV) 400 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal, painted; aluminum casting
Dimensions:	Width: 59.1 cm Depth: 19.9 cm Height: 30.3 cm
Weight:	5.35 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 4 x Ø10mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Material:	Metal, 0.8 mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x barndoor
- 1 x remote control
- 1 x battery
- 1 x user manual