

EUROLITE Zoom4Bar QCL Bar

LED zoom effect bar with RGBW color mixing, incl. IR remote control

Art. No.: 51913896

GTIN: 4026397643619



Features:

- 4 segments for dynamic running lights
- 16 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
4 segments controlled separately
- Zoom motor driven
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 5; 7; 9; 20; 26 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
- Flicker-free
- With a beam angle of 5° - 80°
- With double bracket
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397643619

Weight: 10,25 kg

Length: 0.65 m

Width: 0.20 m

Heigh: 0.36 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 140 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	16 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Zoom motor driven
DMX channels:	5; 7; 9; 20; 26
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; QuickDMX via 5-pin XLR (M) mounting version (optional); master/slave function
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	5° - 80°
Beam angle (1/2 peak):	5 - 75°
Beam angle (1/10 peak):	10 - 80°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 57.5 cm Depth: 19.5 cm Height: 23 cm
Weight:	8.95 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control