

EUROLITE LED IP T-PIX 12 HCL Bar

Weather-proof (IP65) bar with RGBAW+UV color mixing and pixel control

Art. No.: 51914111

GTIN: 4026397670158



Features:

- DMX and power terminals intelligently designed for easy wiring
- 12 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 45 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR 4x6; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; LED EASY OPERATOR DELUXE; Colorchief
- Flicker-free
- With a beam angle of 25°
- With mounting bracket; with omega bracket
- LCD display
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397670158

Weight: 9,15 kg

Length: 1.08 m

Width: 0.19 m

Height: 0.26 m

Technical specifications:

| | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 125 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | 1 x IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 1 - 20 Hz |
| DMX channels: | 6; 11; 24; 41; 77 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; master/slave function; sound to light via microphone |
| Fixtures available for: | LED PC-Control 512; LED EASY OPERATOR 4x6; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; LED EASY OPERATOR DELUXE; Colorchief |
| Projection: | Flicker-free |
| PWM frequency: | 4000 Hz |
| Beam angle: | 25° |
| Beam angle (1/2 peak): | 25° |
| Beam angle (1/10 peak): | 50° |
| Housing color: | Black |
| Attachment system: | 2x mounting bracket Omega bracket |
| Display type: | LCD display |
| Dimensions: | Length: 99 cm Depth: 16 cm Height: 14 cm |
| Weight: | 8.30 kg |
| Noise classification: | Class 0 (no noise at all) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x XLR cable
- 2 x mounting bracket