

EUROLITE LED IP T-PIX 18 QCL Bar

Weatherproof (IP65) bar with RGBW color mixing and pixel control, incl. IR remote control

Art. No.: 51914129

GTIN: 4026397751413



Description:

This weatherproof bar delivers versatile pixel effects across a length of 106.5 centimeters. It features 18 individually controllable LEDs with RGBW color mixing, enabling creative lighting designs. For easier operation, reduced DMX modes with fewer pixels are also available.

With an IP65 rating, the bar is suitable for both permanent installations and outdoor events, even in heavy rain.

Thanks to its fanless design, it operates whisper-quiet and prevents dust from entering the unit, making it an excellent choice for many indoor installation scenarios as well.

Features:

- 18 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Dimmer electronic; color change adjustable
- Wash effect; strobe effect
- 12 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; full on; static; auto)
- With a beam angle of 18°
- With mounting bracket; with bracket for floor use
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397751413

Weight: 7,00 kg

Length: 1.03 m

Width: 0.14 m

Heigh: 0.17 m

- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; stage; restaurants, bars and hotels; installation
- Silent operation
- Application possibility: Suspended
- Fixtures available for Light Captain

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 6; 9; 22; 24; 36; 72
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4100 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	38°
Lamp life:	50000 h
Housing color:	Black
Attachment system:	Mounting bracket 2x bracket for floor use
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 106.5 cm Depth: 13.3 cm Height: 21.0 cm
Weight:	6.40 kg
Noise classification:	Class 0 (no noise at all)

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery
2 x mounting bracket
2 x screw
4 x washer