EUROLITE LED IP PAD 60x3W CW/WW

Weather-proof DMX spotlight (IP65) with 40 x 3 W LED (cold and warm white)

Art. No.: 51914164

GTIN: 4026397461688

Features:

- Equipped with 60 x 3 W LED: 24 x warm white, 36 x cold white
- For architectural lighting
- Suitable for external use (IP65)
- Color temperature steplessly adjustable between 3000 K and 7000 K
- 17 preset color temperatures
- Strobe effect
- Dimmer
- Master/Slave function
- Compact, matt grey housing
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts without power selector
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 60 LEDs 3 W high-power 2in1 CW/WW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- With a beam angle of 45°
- Suitable for outdoor use IP65
- Silent operation

Logistic

EAN / GTIN: 4026397461688

Weight: 9,50 kg

Length: 0.39 m

Width: 0.23 m

Heigth: 0.43 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	160 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Cable length:	1.5 m
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	60 x 3 W high-power 2in1 CW/WW (homogenous color mix)
Flash rate:	1 - 30 Hz
DMX channels:	2; 5
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle (1/2 peak):	45°
Housing color:	Grey
Dimensions:	Width: 34.4 cm Depth: 14 cm Height: 32.6 cm
Weight:	8.40 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR1225 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x adapter cable
1 x remote control

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.