

EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 HCL RGBWA/UV color mixing and frost filters

Art. No.: 51914172

GTIN: 4026397670233



List price: 462.91 €

incl. 19% VAT.

Features:

- 14 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
 - Frost filter
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - Direct color selection for 25 preset colors
 - The device is cooled by passive convection cooling
 - Control via DMX; stand-alone; IR remote control
 - Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
 - Flicker-free
 - With a beam angle of 15°
 - With double bracket
 - LCD display
 - Mains input and output for power linking up to 8 units
 - Suitable for outdoor use IP65
 - For application areas such as: Installation; stage; rental; architecture
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 3 x frost filter, 1 x XLR cable, 2 x knurled screw, 1 x user manual

Logistic

EAN / GTIN: 4026397670233

Weight: 8,10 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	3; 5; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
	27°
	30°
	60°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31 cm
	Depth: 22,5 cm
	Height: 36,5 cm
Weight:	6,80 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Frost filter	
Material:	Plastic, 2 mm
Dimensions:	Diameter: Ø 20,5 cm
XLR cable	
Cable length:	Approx. 1,5 m
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting