

EUROLITE LED IP PAR 3x8W QCL Spot

Weather-proof (IP65) spotlight with 3 x 8 W LED and 4in1 RGBW color mixing

Art. No.: 51914234

GTIN: 4026397683974



Description:

The Eurolite IP Par series offers weatherproof spotlights in various sizes and with different color-mixing options. The IP Par 3x8W QCL is a particularly compact model in this series and stands out for its solid build quality.

With its IP65-rated housing, the spotlight is reliably protected against rain and the elements. The three 8 W LEDs are based on RGBW color mixing.

The flexible double bracket allows for use in floor-standing mode, as a suspended installation, or on a tripod. Weatherproof T-Con connectors are available for power supply, which also allow daisy-chaining to additional devices. DMX control is via three-pin, weatherproof XLR connectors.

Features:

- 3 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography

Logistic

EAN / GTIN: 4026397683974

Weight: 3,20 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.29 m

- Silent operation
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse serviceable
Lamp type:	LED lamp
LED type:	3 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 21.5 cm Depth: 17.1 cm Height: 24.4 cm
Weight:	3.00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual