

## EUROLITE LED IP PAR 3x9W SCL Spot

Weather-proof (IP65) spotlight with 3 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

Art. No.: 51914235

GTIN: 4026397683981



**List price: 236.81 €**

incl. 19% VAT.

### Features:

- 3 powerful LEDs 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Preprogrammed in Light J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: On stand; suspended

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397683981

Weight: 3,20 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.29 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 35 W

IP classification: IP65

Protection class: Protection class I

|                         |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Power connection:       | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Power output:           | IP T-Con (F) mounting version                                                                  |
| LED type:               | 3 x 9 W 7in1 SCL RGB/CW/WW/A/UV<br>(homogenous color mix)                                      |
| Flash rate:             | 0 - 20 Hz                                                                                      |
| DMX channels:           | 3; 5; 7; 9; 13                                                                                 |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                              |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                              |
| Cooling:                | Passive convection cooling                                                                     |
| Control:                | Stand-alone; IR remote control; DMX                                                            |
| Preprogrammed in:       | Light J; EASY SHOW 1; Light Captain; EASY<br>SHOW 2; EASY SHOW 3                               |
| Projection:             | Flicker-free                                                                                   |
| Beam angle:             | 15°                                                                                            |
| Beam angle (1/2 peak):  | 15°                                                                                            |
| Beam angle (1/10 peak): | 30°                                                                                            |
| Housing color:          | Black                                                                                          |
| Attachment system:      | Double bracket                                                                                 |
| Display type:           | LCD display                                                                                    |
| Dimensions:             | Width: 21,5 cm<br>Depth: 17,1 cm<br>Height: 24,4 cm                                            |
| Weight:                 | 3,00 kg                                                                                        |
| Noise classification:   | Class 0 (no noise at all)                                                                      |
| Photobiological safety: | Risk Group 0                                                                                   |
| Remote control          |                                                                                                |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese<br>built-in                                     |
| Legal specifications    |                                                                                                |
| Special product:        | Not designed for household room illumination                                                   |
| Intended use:           | Show effect lighting                                                                           |