

EUROLITE LED IP PAR 9 UV Spot

Weather-proof (IP65) PRO UV spotlight with 9 UV LEDs (365nm), incl. IR remote control

Art. No.: 51914255

GTIN: 4026397697179



List price: 593.81 €

incl. 19% VAT.

Features:

- Minimum visible light
- High output at full intensity
- 9 powerful LEDs 3 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- 4 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; master/slave function
- Preprogrammed in Light Captain; Light´J; Colorchief
- With a beam angle of 20°
- With double bracket
- LCD display
- Suitable for outdoor use
- For application areas such as: Clubs/dancing school; installation; theater; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397697179

Weight: 5,40 kg

Length: 0.38 m

Width: 0.33 m

Height: 0.20 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 30 W

IP classification: IP65

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F)
LED type:	9 x 3 W high-power ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; master/slave function
Preprogrammed in:	Light Captain; Light´J; Colorchief
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	50
Wavelength:	370 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28,90 cm Depth: 15,25 cm Height: 33,80 cm
Weight:	4,87 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting