

## EUROLITE LED IP FL-100 SMD RGB

Outdoor floodlight (IP65) with RGB LEDs and IR remote control

Art. No.: 51914609

GTIN: 4026397715897



### Features:

- Extremely slim housing in an appealing design
- 108 LEDs SMD 2835 R/G/B
- Color change automatic; program selection manual; color selection manual; color fade adjustable; program speed adjustable; Dimmer electronic
- Direct color selection for 16 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control
- With a beam angle of 70°
- With mounting bracket
- Suitable for outdoor use IP65
- For application areas such as: Architecture; decoration; party room; advertisement/Shop window
- Application possibility: Suspended
- Silent operation

### Logistic

EAN / GTIN: 4026397715897

Weight: 2,05 kg

Length: 0.32 m

Width: 0.28 m

Height: 0.04 m

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Cable construction:	3 x 1.0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	108 x SMD 2835 R/G/B
Cooling:	Passive convection cooling
Control:	IR remote control
Beam angle:	70°
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color of light:	Switching colors
Luminous flux:	4479 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 30.00 cm Depth: 4.2 cm Height: 24.5 cm
Weight:	1.92 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1509778
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

### Scope of delivery:

- 1 x device
- 1 x remote control
- 1 x battery
- 2 x user manual