

EUROLITE LED IP FL-20 SMD CW
Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915015
GTIN: 4026397695816



Features:

- 30 LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- For application areas such as: Architecture; decoration; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397695816
Weight: 0,40 kg
Length: 0.16 m
Width: 0.07 m
Heigh: 0.12 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	22 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1 m

Lamp type:	LED lamp
LED type:	30 x SMD 2835 cold white (CW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color temperature:	6000K
Color rendering index (CRI):	80 Ra
Luminous flux:	1756 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 13 cm Depth: 2.3 cm Height: 10 cm
Weight:	0.36 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	963751
Diameter mounting holes:	1 x Ø8mm; 2 x Ø6mm
Material:	Metal, 1.5 mm

Scope of delivery:

1 x device
1 x user manual