

EUROLITE LED IP FL-100 SMD WW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915040 GTIN: 4026397695915











List price: 71.28 €

incl. 19% VAT.

Features:

- 128 powerful LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

- 1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397695915

Weight: 1,25 kg Length: 0.28 m Width: 0.06 m Heigth: 0.24 m

Technical specifications:

| Power supply: | 230 V AC, 50 Hz |
|---------------------|--|
| Power consumption: | 100 W |
| IP classification: | IP66 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1,0 mm ² H05RN-F |
| Cable length: | Approx. 1 m |

| Lamp type: | LED lamp |
|----------------------------------|--------------------------------|
| LED type: | 128 x SMD 2835 warm white (WW) |
| Cooling: | Passive convection cooling |
| Control: | Plug and play |
| Beam angle (1/2 peak): | 70° |
| Beam angle (1/10 peak): | 120° |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 82 Ra |
| Luminous flux: | 8899 lm |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Material: | Aluminum casting |
| Dimensions: | Width: 27,3 cm |
| | Depth: 3,2 cm |
| | Height: 25 cm |
| Weight: | 1,17 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 966470 |
| Mounting bracket | |
| Diameter mounting holes: | 3 x Ø8mm |
| Material: | Metal, 2 mm |
| | |