

EUROLITE LED IP FL-100 SMD CW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915045

GTIN: 4026397695830



Features:

- 128 LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- For application areas such as: Architecture; decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Silent operation
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397695830

Weight: 1,20 kg

Length: 0.28 m

Width: 0.24 m

Height: 0.06 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	100 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp

LED type:	128 x SMD 2835 cold white (CW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120
Color temperature:	6000K
Luminous flux:	9364 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 27.3 cm Depth: 3.2 cm Height: 25 cm
Weight:	1.12 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	E
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm

Scope of delivery:

- 1 x device
- 1 x user manual