

EUROLITE LED SLS-10 Hybrid HCL

Flat spotlight with RGBWA+UV LEDs (6in1) and strobe

Art. No.: 51915271

GTIN: 4026397628661



The article is no longer in our assortment.

Features:

- 9 high-power 10 W 6in1 LEDs for RGBWA color mixing and blacklight
- 36 white 0.5 W LEDs for dynamic strobe effects
- 18 additional 0.2 W RGB LEDs for dynamic color and strobe effects
- Built-in auto and music show programs
- Direct color selection for 22 preset colors
- Individual control of all RGBWA+UV and strobe LEDs for use as blacklight, stroboscope or PAR spotlight
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Flat housing form requires minimal space when rigging
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- 18 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- 36 powerful LEDs 0,5 W SMD 5050 cold white (CW)
- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512
- With a beam angle of 28°

Package contents

- 1 x remote control

Logistic

EAN / GTIN: 4026397628661

Weight: 2,23 kg

Length: 0.30 m

Width: 0.28 m

Height: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix) 36 x 0,5 W SMD 5050 cold white (CW) 9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	1; 3; 6; 9; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512
Beam angle:	28°
Beam angle (1/2 peak):	28°
Beam angle (1/10 peak):	54°
Housing color:	Black
Dimensions:	Width: 25,5 cm Depth: 12 cm Height: 28,5 cm
Weight:	1,90 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting