

EUROLITE LED SLS-12 UV Floor

LED floor spot with 12 x 1 W UV LEDs, incl. IR remote control

Art. No.: 51915283 GTIN: 4026397696738









List price: 83.18 €

incl. 19% VAT.

Features:

- Slim design for space-saving applications
- 12 powerful LEDs 1 W ultra violet (UV)
- The device is cooled by passive convection cooling
- Control via QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional);
 CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; Light'J; Colorchief
- Flicker-free
- With a beam angle of 12°
- With double bracket
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	14 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397696738

Weight: 0,93 kg Length: 0.17 m Width: 0.17 m Heigth: 0.18 m

Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
LED type:	12 x 1 W ultra violet (UV)
Flash rate:	0,5 - 23 Hz
DMX channels:	1; 3; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Light´J; Colorchief
Projection:	Flicker-free
PWM frequency:	2000 Hz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	24°
. ,	
Housing color:	Black
	Black Double bracket
Housing color:	
Housing color: Attachment system:	Double bracket
Housing color: Attachment system: Display type:	Double bracket 4 digit 7-segment LED display
Housing color: Attachment system: Display type: Transport aid:	Double bracket 4 digit 7-segment LED display Rubber feet
Housing color: Attachment system: Display type: Transport aid: Material:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions: Weight: Noise classification:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg Class 0 (no noise at all)
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions: Weight: Noise classification: Photobiological safety:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg Class 0 (no noise at all)
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions: Weight: Noise classification: Photobiological safety: Remote control	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg Class 0 (no noise at all) Risk Group 0 1 x button cell 3.0 V CR2025 lithium manganese
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions: Weight: Noise classification: Photobiological safety: Remote control Battery:	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg Class 0 (no noise at all) Risk Group 0 1 x button cell 3.0 V CR2025 lithium manganese
Housing color: Attachment system: Display type: Transport aid: Material: Dimensions: Weight: Noise classification: Photobiological safety: Remote control Battery: Legal specifications	Double bracket 4 digit 7-segment LED display Rubber feet ABS Acrylonitrile butadiene styrene Width: 18,2 cm Depth: 9,8 cm Height: 17,8 cm 0,78 kg Class 0 (no noise at all) Risk Group 0 1 x button cell 3.0 V CR2025 lithium manganese built-in