

## EUROLITE LED SLS-12 QCL Floor

LED floor spot with 4in1 QCL RGBW color mixing, incl. IR remote control

Art. No.: 51915383

GTIN: 4026397696714



### Features:

- Slim design for space-saving applications
- 12 LEDs 8 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone; sound to light; DMX; master/slave function
- Fixtures available for EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- With a beam angle of 16°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397696714

Weight: 1,95 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.23 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 40 W

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
Lamp type:	LED lamp
LED type:	12 x 8 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	4; 6; 8
Cooling:	1 x cooling fan
Control:	QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone; sound to light; DMX; master/slave function
Fixtures available for:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
PWM frequency:	2000 Hz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 26.0 cm Depth: 12.5 cm Height: 23.3 cm
Weight:	1.70 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1.2 m
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### Scope of delivery:

1 x spotlight  
1 x power cord  
1 x remote control  
1 x user manual