

EUROLITE LED SLS-7 HCL Floor white

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

Art. No.: 51915391 GTIN: 4026397669930













List price: 129.71 €

incl. 19% VAT.

Features:

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function
- Preprogrammed in Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light'J; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- With double bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- Application possibility: Standing; suspended; on stand
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397669930

Weight: 1,61 kg Length: 0.25 m Width: 0.24 m Heigth: 0.15 m

Technical specifications:

recimical specifications.			
Power supply:	100-240 V AC, 50/60 Hz		
Power consumption:	20 W		
IP classification:	IP20		
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)		
Power output:	1 x IEC connector (F) mounting version		
Fuse:	T 0,5 A		
Lamp type:	LED lamp		
LED type:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)		
Flash rate:	0 - 20 Hz		
DMX channels:	2; 3; 4; 6; 10		
DMX input:	3-pin XLR (M) mounting version		
DMX output:	3-pin XLR (F) mounting version		
Cooling:	Cooling fan		
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function		
Preprogrammed in:	Light Captain; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light'J; EASY SHOW 2; EASY SHOW 3; Colorchief		
Projection:	Flicker-free		
Beam angle:	17°		
Beam angle (1/2 peak):	17°		
Housing color:	White		
Attachment system:	Double bracket		
Display type:	4 digit 7-segment LED display		
Transport aid:	Rubber feet		
Material:	ABS Acrylonitrile butadiene styrene		
Dimensions:	Width: 22 cm Depth: 11 cm		
	Height: 21 cm		
Weight:	1,38 kg		
Noise classification:	Class 2 (slight noise)		
Photobiological safety:	Risk Group 0		
Mounting bracket			
Diameter mounting holes:	5 x Ø11mm		
Material:	Metal, 2 mm		
Color:	White		
Power cord			
Cable construction:	3 x 0,75 mm² H05VV-F		
Cable length:	Approx. 1,2 m		
Color:	White		

_							
ь	20	m	വ	Δ	CO	nt	r

Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in