

EUROLITE LED TL-3 TCL 3x3W Trusslight

Spot with 3 x 3 W RGB LEDs, mounting hole and IR remote control

Art. No.: 51915450

GTIN: 4026397509410



The article is no longer in our assortment.

Features:

- Compact and bright, making it perfect for truss installation
- Equipped with 3 x 3 W 3in1LED in the colors red, green and blue
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Convenient control possible via IR remote control (optional accessory)
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSSE 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via IR remote control (optional); stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With a beam angle of 16°

Logistic

EAN / GTIN: 4026397509410

Weight: 1,00 kg

Length: 0.16 m

Width: 0.15 m

Height: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12,00 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 8
Cooling:	Passive convection cooling
Control:	IR remote control (optional); stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34°
Housing color:	Black
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 10,4 cm
Weight:	0,90 kg
DMX connection:	3-pin XLR
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting