

## EUROLITE LED PST-10 QCL Spot

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916152

GTIN: 4026397690132



### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 LED 10 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 4°
- With double bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397690132

Weight: 1,20 kg

Length: 0.15 m

Width: 0.15 m

Height: 0.29 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 12 W

Protection class: Protection class II

|                          |   |
|--------------------------|---|
| Power connection:        | Fixed power supply cord with Euro plug  |
| Cable construction:      | 2 x 0.75 mm <sup>2</sup> H05VVH2-F  |
| Cable length:            | Approx. 1 m   |
| Fuse:                    | 5 x 20 mm, T 0.5 A fuse replaceable   |
| Lamp type:               | LED lamp  |
| LED type:                | 1 x 10 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)                             |
| Flash rate:              | 0.5 - 24 Hz   |
| DMX channels:            | 3; 4; 5; 6; 9   |
| Cooling:                 | Passive convection cooling  |
| Control:                 | IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function |
| Fixtures available for:  | Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Colorchief                          |
| Projection:              | Flicker-free  |
| PWM frequency:           | 23400 Hz  |
| Beam angle (1/2 peak):   | Spot 4°<br>Frost filter 16°   |
| Beam angle (1/10 peak):  | Spot 7°<br>Frost filter 36°   |
| Color temperature:       | 6500K   |
| Housing color:           | Black   |
| Attachment system:       | Double bracket  |
| Display type:            | 4 digit 7-segment LED display   |
| Material:                | Plastic   |
| Dimensions:              | Length: 20.2 cm<br>Width: 16.3 cm<br>Height: 20.3 cm                                      |
| Weight:                  | 1.03 kg   |
| Noise classification:    | Class 0 (no noise at all)   |
| Photobiological safety:  | Risk Group 0  |
| Diameter mounting holes: | 1 x Ø11mm   |
| Material:                | Metal, 2 mm   |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                   |
| Material:                | Plastic, 1 mm   |
| Dimensions:              | Diameter: Ø 7.7 cm  |
| Special product:         | Not designed for household room illumination  |
| Intended use:            | Show effect lighting  |

### Scope of delivery:

- 1 x spotlight
- 1 x remote control
- 1 x battery
- 1 x frost filter
- 1 x lamp clamping ring
- 1 x user manual