

EUROLITE LED PST-40 QCL Spot

LED spotlight with RGBW color mixing, IR remote control and 2 frost filters

Art. No.: 51916170

GTIN: 4026397710625



Description:

This compact fixture is a powerful pinspot with versatile applications. A 40 W LED with RGBW color mixing produces a precise, narrow 4° beam, making it ideal for applications such as illuminating mirror balls.

Thanks to its fanless design, the unit operates completely silently and is well suited for noise-sensitive environments. The included frost filters allow the beam angle to be expanded to 20° or even 80°, enabling the fixture to be used as a compact spot or floodlight.

Despite its small size, the fixture offers extensive connectivity: P-Con power input and output, 3-pin XLR connectors for DMX control, and a WDMX USB port for easy upgrades to wireless DMX systems such as QuickDMX or CRMX.

Features:

- Two additional frost filters provide a soft, homogeneous light
- 1 LED 40 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
- Fixtures available for Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief

Logistic

EAN / GTIN: 4026397710625

Weight: 2,22 kg

Length: 0.19 m

Width: 0.17 m

Height: 0.28 m

- Flicker-free
- With a beam angle of 4°
- With double bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand
- remote control**
- 24 buttons on the remote control for saving your own settings

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 36 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 1 x 40 W 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 0.8 - 22 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function |
| Fixtures available for: | Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 4° |
| Beam angle (1/2 peak): | 4° Frost filter 20° Frost filter 80° |
| Beam angle (1/10 peak): | 8° |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | OLED display |
| Material: | Plastic; metal |
| Dimensions: | Length: 12 cm Width: 17 cm Height: 22.5 cm |
| Weight: | 1.98 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 1 x Ø11mm; 3 x Ø2mm |

| | |
|---------------------|---|
| Material: | Metal, 2 mm |
| Cable construction: | 3 x 1.0 mm ² H05VV-F |
| Cable length: | Approx. 1.2 m |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Material: | Plastic, 3 mm |
| Dimensions: | Width: 12 cm Height: 10.8 cm |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x frost filter
- 1 x user manual