


EUROLITE LED RETRO 6 Bar ABL

Warm white blinder with additional colored LEDs for atmospheric lighting

Art. No.: 51916645

GTIN: 4026397755725



List price: 296.31 €

incl. 19% VAT.

Description:

This 100 cm bar combines modern lighting technology with a distinctive retro look. Six powerful LED strips produce a very warm, almost orange-toned white light.

Each strip is equipped with a 60 W LED and can be controlled individually. The reflective sections between them are illuminated by a total of 120 RGB LEDs, which are divided into 12 segments and can be controlled individually.

A range of DMX modes is available. In the most advanced mode, all elements can be controlled individually, while reduced modes still offer a wide variety of effects even with smaller DMX controllers.

The series is complemented by a matching spot fixture that delivers the same effects in a different form factor.

Features:

- 6 LEDs 60 W COB (chip-on-board) amber (A)
 LEDs controlled separately
- 120 LEDs 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
10 segments controlled separately
- Blinder effect; strobe effect
- With a beam angle of 120°
- Silent operation
- The device is cooled by temperature-controlled fan
- With bracket for floor use; with omega bracket
- Application possibility: Standing; suspended
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector

Logistic

EAN / GTIN: 4026397755725

Weight: 5,85 kg

Length: 1.05 m

Width: 0.17 m

Height: 0.24 m

- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; stage; theater; mobile djs / entertainer; restaurants, bars and hotels; rental
- Flicker-free
- 3 integrated show programs
- Dimmer electronic
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 4 digit 7-segment LED display
- Fixtures available for Light Captain

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	6 x 60 W COB (chip-on-board) amber (A) 120 x 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
Flash rate:	0.8 - 20 Hz
DMX channels:	12; 16; 43
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	2 x temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	120°
Beam angle (1/2 peak):	120°
Beam angle (1/10 peak):	120°
Color temperature:	1800K
Housing color:	Black
Attachment system:	Bracket for floor use Omega bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Use of brands:	Built with SEETRONIC connector
Material:	Metal
Dimensions:	Width: 100.0 cm Depth: 14.0 cm

Height: 15.0 cm

Weight: 5.10 kg

Noise classification: Class 0 (no noise at all)

Special product: Not designed for household room illumination

Intended use: Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x omega bracket