

EUROLITE LED SCY-5 Hybrid Beam Effect

LED spotlight with twofold effects: 3in1 TCL RGB LEDs, dynamic color effects and strobe

Art. No.: 51918671

GTIN: 4026397628241



Features:

- Individual control of all RGB+UV and RGB strobe LEDs for use as blacklight, stroboscope or PAR spotlight
- 30 LEDs 0.2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
10 segments controlled separately
- 5 LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Fan effect; strobe effect; UV effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; sound to light via microphone; DMX; master/slave function
- Fixtures available for Colorchief
- With a beam angle of 25°
- With mounting bracket
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397628241

Weight: 2,30 kg

Length: 0.33 m

Width: 0.28 m

Height: 0.13 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

IP classification: IP20

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	30 x 0.2 W SMD 5050 3in1 TCL RGB (homogenous color mix) 5 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	1; 4; 20
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; sound to light via microphone; DMX; master/slave function
Fixtures available for:	Colorchief
Beam angle:	25°
Beam angle (1/2 peak):	25°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Width: 19.7 cm Depth: 27.9 cm Height: 18 cm
Weight:	2.00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x light effect
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery