

EUROLITE LED BP-9 Panel RGBW+CW

LED spotlight with 9 individually controllable beams and 4 additional strobe strips

Art. No.: 51930261

GTIN: 4026397753691



List price: 165.41 €

incl. 19% VAT.

Description:

This fixture offers more than meets the eye. Nine lenses focus the light into an extremely narrow 2° beam. Behind each lens is a 12-watt RGBW LED, and each can be controlled individually, creating a powerful beam matrix.

The system is complemented by 72 cold white LEDs positioned between the lenses. These are arranged in four controllable lines and are designed for strobe and blinder effects.

For control, multiple DMX modes are available. In the most advanced mode with 43 DMX channels, all functions can be controlled individually. Alternatively, reduced modes with 6 or 12 channels still offer a wide range of creative possibilities.

Features:

- 9 LEDs 12 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- 72 LEDs 0.5 W SMD 5730 cold white (CW)
 4 segments controlled separately
- Dimmer electronic; color blend stepless; foreground color; background color
- Beam effect; strobe effect
- 9 integrated show programs
- Direct color selection for 31 preset colors
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- DMX fail mode (hold; blackout)
- With a beam angle of 2°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397753691

Weight: 2,95 kg

Length: 0.23 m

Width: 0.16 m

Height: 0.23 m

- The device is cooled by cooling fan
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- Fixtures available for Light Captain

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	9 x 12 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 72 x 0.5 W SMD 5730 cold white (CW)
Flash rate:	0.8 - 20 Hz
DMX channels:	6; 12; 43
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light Captain
PWM frequency:	7000 Hz
DMX fail mode:	Hold; blackout
Beam angle:	2°
Beam angle (1/2 peak):	Beam 2°
Beam angle (1/10 peak):	Beam 7°
Lamp life:	50000 h
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Diameter mounting holes:	1 x Ø12mm
Material:	Metal
Dimensions:	Width: 26.1 cm Depth: 10.5 cm Height: 26.4 cm
Weight:	2.75 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x user manual
- 2 x mounting bracket
- 2 x knurled screw
- 4 x washer