

EUROLITE LED BBS-5 Bar

LED beam bar with TILT movement and 7 W LEDs

Art. No.: 51930271

GTIN: 4026397508444



The article is no longer in our assortment.

Features:

- Stepless vertical movement via control panel or DMX
- Equipped with five 5 x CREE XM-L 7W cold white LEDs
- 7, 8 or 12 DMX channels selectable
- Each LED can be controlled individually
- Suitable for pixel mapping applications
- Perfect as beam effect into the audience
- Standing or hanging installation possible
- Functions: Built-in programs, dimmer and strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Automatic position correction
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity via Control Board
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LED display and four operating buttons with 14 segment display
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- Preprogrammed in Light J

Logistic

EAN / GTIN: 4026397508444

Weight: 5,80 kg

Length: 0.74 m

Width: 0.15 m

Height: 0.25 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60,00 W
Preprogrammed in:	Light J
Dimensions:	Width: 66,3 cm Depth: 8 cm Height: 14,3 cm
DMX channels:	7/8/12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	30 Hz
LED type:	CREE XM-L 7W cold white
LED number:	5
Maximum TILT-movement:	240°
Beam angle:	2°
Color temperature:	6300-7000 K
Dimensions (L x W x H):	663 x 80 x 143 mm
Weight:	5.10 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting