

EUROLITE LED CBB-2 WW/CW Fairlight

LED light effect bar with WW/CW COB LEDs, incl. IR remote control

Art. No.: 51930272

GTIN: 4026397686746



List price: 320.11 €

incl. 19% VAT.

Features:

- 2 powerful LEDs 50 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
 - Dimmer electronic
 - Strobe effect
 - Integrated show programs
 - Direct color selection for 27 preset colors
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light Captain; Colorchief
 - Flicker-free
 - With a beam angle of 40°
 - Variable color temperature 2400 K - 5000 K
 - Very high color rendering index (CRI)
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Trade fair construction; theater; video and photography
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397686746

Weight: 4,00 kg

Length: 0.30 m

Width: 0.32 m

Height: 0.21 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Protection class:	Protection class I
Lamp type:	LED lamp
LED type:	2 x 50 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40°
Beam angle (1/10 peak):	75°
Color temperature:	2400K - 5000K adjustable
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 928 lx, 3m: 123 lx, 6m: 36 lx Cold white (CW) 1m: 1662 lx, 3m: 220 lx, 6m: 65 lx All 1m: 2522 lx, 3m: 331 lx, 6m: 97 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal; aluminum casting; plastic
Dimensions:	Width: 26,6 cm Depth: 16,95 cm Height: 19,4 cm
Weight:	3,57 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Barndoor	
Material:	Metal, 0,8 mm
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 2 x Ø8mm
Material:	Metal, 2,5 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting