

EUROLITE LED PMB-8 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

Art. No.: 51930288

GTIN: 4026397689181



List price: 593.81 €

incl. 19% VAT.

Features:

- 8 powerful LEDs 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - Integrated show programs
 - Direct color selection for 27 preset colors
 - The device is cooled by low-noise cooling fan
 - Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light´J; Light Captain
 - Flicker-free
 - With a beam angle of 45°
 - With mounting bracket
 - LCD display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Wedding/gala/events; Trade fair and shop fitting; stage; theater; rental
 - Very quiet working noise
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397689181

Weight: 9,80 kg

Length: 1.05 m

Width: 0.26 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 12; 32; 36
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	74°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Length: 98,0 cm Depth: 16,3 cm Height: 20,6 cm
Weight:	8,65 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 3 x Ø10mm; 4 x Ø8mm; 2 x Ø6mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m
Remote control	

Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting