

EUROLITE LED BAR-8 Swing QCL bar

Tilttable LED light effect bar with 8 beams and strobe effect

Art. No.: 51930385

GTIN: 4026397711417



List price: 474.81 €

incl. 19% VAT.

Features:

- Vertical inclination angle adjustable
- Dimmer electronic; color fade; color change; color blend adjustable; color selection
- Strobe effect; uplight effect; multi beam effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
- Preprogrammed in Colorchief; Light Captain
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental
- Very quiet working noise
- Application possibility: Standing; suspended

spotlight

- 8 powerful LEDs 8 W high-power 4in1 QCL RGBW
8 segments controlled separately
- With a beam angle of 1°

strobes

- 175 powerful LEDs 0,2 W SMD 5050 cold white (CW)
7 segments controlled separately
- With a beam angle of 120°

Package contents

- 1 x light effect, 1 x mounting bracket, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397711417

Weight: 8,15 kg

Length: 1.05 m

Width: 0.14 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Max. TILT movement:	215° positioning
Flash rate:	0,35 - 20 Hz
DMX channels:	8; 12; 23; 27; 49
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX via USB (optional); master/slave function; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone
Preprogrammed in:	Colorchief; Light Captain
Projection:	Flicker-free
PWM frequency:	7800 Hz
Illuminance in Lux (lx):	Cold white (CW) 1m: 8183 lx, 3m: 1527 lx, 6m: 372 lx Cold white (CW) 1m: 66 lx, 3m: 9 lx, 6m: 2 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Dimensions:	Length: 100,0 cm Depth: 10,7 cm Height: 25,1 cm
Weight:	7,30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Strobes	
LED type:	175 x 0,2 W SMD 5050 cold white (CW)
Beam angle:	120°
Beam angle (1/2 peak):	120°
Spotlight	
LED type:	8 x 8 W high-power 4in1 QCL RGBW
Beam angle:	1°
Beam angle (1/2 peak):	1° multicolor

Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting