

EUROLITE LED BAR-3 HCL Bar

Compact (26 cm) bar with 3 x 12 W 6in1 LED and RGBWA+UV color mixing

Art. No.: 51930395

GTIN: 4026397617177



Features:

- 3 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Fixtures available for EASY SHOW 3; EASY SHOW 2; Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; decoration; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397617177

Weight: 1,28 kg

Length: 0.28 m

Width: 0.12 m

Heigh: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 12 W

Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	3 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	EASY SHOW 3; EASY SHOW 2; Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	40°
Wavelength:	Ultra violet (UV) 400 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic hard
Dimensions:	Length: 26.5 cm Depth: 8.7 cm Height: 12.9 cm
Weight:	1.13 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm; 4 x Ø8mm; 2 x Ø5mm
Material:	Metal, 2 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x light effect
1 x power cord
1 x remote control
1 x battery
1 x user manual