

EUROLITE LED Strobe SMD PRO 864 DMX RGB

3in1 LED effect light with RGB color mixing

Art. No.: 52200918

GTIN: 4026397696141



Features:

- 864 LEDs 0.2 W SMD 5050 3in1 R/G/B (homogenous color mix)
18 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; running light with two adjustable colors
- Strobe effect; wash effect; Blinder effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light
- Flicker-free
- With mounting bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397696141

Weight: 5,17 kg

Length: 0.47 m

Width: 0.28 m

Height: 0.20 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 175 W

Protection class: Protection class II

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	864 x 0.2 W SMD 5050 3in1 R/G/B (homogenous color mix)
DMX channels:	5; 13; 54
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 46.0 cm Depth: 13.5 cm Height: 22.5 cm
Weight:	4.51 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual