

EUROLITE LED IP PIX Strobe RGB CW+WW MK2

Outdoor spotlight (IP65) for stroboscope, ambient and animation effects

Art. No.: 52200939

GTIN: 4026397742985



Description:

The MK2 version of the IP PIX Strobe is largely identical to the original model. The first version already proved itself with high output, solid build quality, a weatherproof housing, and excellent value for money.

The main update is the mounting bracket: it is now longer, allowing for better cable management when mounted horizontally. It also features a mount for the included omega bracket with quick-release fasteners. Alternatively, a clamp can still be attached directly to the bracket. The MK2 version is available with either 5-pin DMX connectors or, as in this version, 3-pin connectors.

The proven lighting concept remains unchanged: at the center is a very bright LED strip with adjustable color temperature from warm white to cool white, divided into four individually controllable segments. This is complemented by RGB LEDs above and below, arranged in eight segments.

With its extremely wide beam angle and excellent side visibility, the fixture can be used as a strobe, a blinder, or for atmospheric lighting effects. Its fanless design ensures completely silent operation, while the hermetically sealed IP65 housing provides reliable protection against dust and weather, making it suitable for both indoor and outdoor use.

Features:

- Compact and bright
- Show programs for white and colored LEDs on separate DMX channels
- 240 LEDs 0.5 W SMD 5050 3in1 TCL RGB
8 segments controlled separately
- 40 LEDs 1 W SMD 3030 2in1 BCL CW/WW
4 segments controlled separately
- With a beam angle of 120°

Logistic

EAN / GTIN: 4026397742985

Weight: 4,13 kg

Length: 0.41 m

Width: 0.24 m

Height: 0.14 m

- Strobe effect; wash effect; ambient effect
- Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; color animations with two adjustable colors
- 20 integrated show programs
- Variable color temperature 3200 K - 6600 K
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- Fixtures available for Light J; Light Captain; GDTF (GrandMA3)
- Flicker-free
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- The device is cooled by passive convection cooling
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; theater; rental; architecture
- Silent operation
- Application possibility: Standing; suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	240 x 0.5 W SMD 5050 3in1 TCL RGB 40 x 1 W SMD 3030 2in1 BCL CW/WW
Flash rate:	1 - 25 Hz
DMX channels:	6; 10; 18; 24; 25; 32
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX
Fixtures available for:	Light J; Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle (1/2 peak):	120°
Color temperature:	3200K - 6600K adjustable
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 38 cm Depth: 11 cm Height: 17.6 cm

Weight:	3.68 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	3 x Ø13mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.5 mm ² H07RN-F
Cable length:	Approx. 1.2 m
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x omega bracket