

## EUROLITE LED SLS-98 Strobe SMD

Compact strobe with 98 SMD LEDs & DMX, each ring individually controllable

Art. No.: 52201092

GTIN: 4026397613346



### Description:

This compact strobe light in a slim-line design is equipped with a total of 98 flicker-free SMD 5030 LEDs and offers you both strobe and blinder effects. The flash frequency is 1-20 flashes per second. The strobe can be operated in stand-alone mode, with a DMX controller or by sound control via the built-in microphone. Delivery includes an IR remote control for convenient operation from a distance.

In DMX mode, the 5 ring-shaped LED segments can be controlled individually or in groups. You can choose from two DMX modes with 4 or 9 channels respectively. The fixture has 3-pin DMX connectors as well as an IEC input to connect it to the mains and a feed-through output for daisy-chaining up to 8 units.

### Features:

- Flat version requires minimal space when mounting
- 98 LEDs SMD 5730 cold white (CW) (homogenous color mix) <BR>5 segments controlled separately
- Dimmer electronic
- Strobe effect; Blinder effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Fixtures available for LED PC-Control 512; Light Captain
- Flicker-free
- With double bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental

### Logistic

EAN / GTIN: 4026397613346

Weight: 1,45 kg

Length: 0.27 m

Width: 0.23 m

Height: 0.16 m

- Very quiet working noise
- Application possibility: Standing; suspended

## Technical specifications:

|                          |  |
|--------------------------|--|
| Power supply:            | 100-240 V AC, 50/60 Hz   |
| Power consumption:       | 24 W   |
| Protection class:        | Protection class II  |
| Power connection:        | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:            | 1 x IEC connector (F) mounting version   |
| Fuse:                    | 5 x 20 mm, F 1 A fuse replaceable  |
| Lamp type:               | LED lamp   |
| LED type:                | 98 x SMD 5730 cold white (CW) (homogenous color mix)   |
| Flash rate:              | 0 - 20 Hz  |
| DMX channels:            | 4; 9   |
| DMX input:               | 1 x 3-pin XLR (M) mounting version   |
| DMX output:              | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                 | Cooling fan  |
| Control:                 | Stand-alone; DMX; sound to light via microphone; IR remote control                               |
| Fixtures available for:  | LED PC-Control 512; Light Captain  |
| Projection:              | Flicker-free   |
| Attachment system:       | Double bracket   |
| Material:                | Plastic  |
| Dimensions:              | Width: 21.5 cm<br>Depth: 12 cm<br>Height: 24.5 cm  |
| Weight:                  | 1.20 kg  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments)                           |
| Diameter mounting holes: | 3 x Ø11mm  |
| Material:                | Metal, 2 mm  |
| Cable construction:      | 3 x 0.75 mm <sup>2</sup> H05VV-F   |
| Cable length:            | Approx. 1.2 m  |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in  |
| Special product:         | Not designed for household room illumination   |
| Intended use:            | Show effect lighting   |

## Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual