

ALUTRUSS Gizmo/Clamps Truss Adapter black

Truss mount

Art. No.: 60320385

GTIN: 4026397570458



Features:

- With two TPC-50 clamps
- Trusspipe: 50 mm
- <p>ALUTRUSS GI-1 Truss Adapter black
- <h2 class="featureSatz">Truss mount</h2>U-profile for hanging truss from the ceiling
- Designed for trusses from 25 to 40 cm
- Thanks to its adjustable system, just one adapter can be used for different trusses
- M20 ring bolt with washer and self-locking nut
- LGA tested
- <p>EUROLITE TPC-50S Half Coupler
- <h2 class="featureSatz">Mounting coupler for 50 mm tube, maximum load WLL 800 kg</h2>

Logistic

EAN / GTIN: 4026397570458
Weight: 3,90 kg
Length: 0.41 m
Width: 0.31 m
Heigh: 0.28 m

Technical specifications:

Trusspipe:	50 mm
Weight:	3.98 kg

ALUTRUSS GI-1 Truss Adapter black

Maximum load BGV C1 (8-fold):	250 kg
-------------------------------	--------

Maximum load WLL (4-fold):	500 kg
Color:	Black
Material thickness:	3.5 mm
Dimensions:	Length: 40 cm Width: 8 cm Height: 5 cm
Weight:	2.57 kg

EUROLITE TPC-50S Half Coupler

Maximum load BGV C1 (8-fold):	400 kg
Maximum load WLL (4-fold):	800 kg
Tube diameter sector:	45 - 50 mm
Material:	Aluminum
Color:	Black
Mounting screw:	M10
Dimensions:	Length: 11 cm Width: 5 cm Depth: 11.50 cm
Weight:	0.71 kg

Scope of delivery:

1 x device
1 x user manual