

EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

Art. No.: 70064502

GTIN: 4026397392289



Description:

The EUROLITE DMX LED Operator 2 is a DMX controller especially designed for the EUROLITE LED-spots and LED-effects with 6 DMX-channels. This controller features pre-programmed presets and colors, which can easily be displayed by pressing one button. Save your precious time for programming the individual DMX-channels in order to display this color or that color. Furthermore, you can control one smoke-machine with 2 DMX-channels by pressing a button.

Logistic

EAN / GTIN: 4026397392289

Weight: 1,34 kg

Length: 0.36 m

Width: 0.21 m

Height: 0.11 m

Features:

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Can transmit up to 8 DMX channels
- Control via DMX; sound to light via microphone

- Desktop console housing

Technical specifications:

Pin configuration:	Inside + / outside -
Power consumption:	4.00 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 8
Control:	DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 26.5 cm Depth: 16.5 cm Height: 5.5 cm
Weight:	1.12 kg
Power supply:	230 V AC, 50 Hz, via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector

Scope of delivery:
