

EUROLITE DMX Split/Boost 8 PRO 3-pin

2 in/8 out DMX splitter/merger with RDM support and real-time DMX monitoring

Art. No.: 70064834

GTIN: 4026397735536



Features:

- DMX modes: LTP, HTP, merge or backup
- (19") 48.3 cm rack installation 1 U
- Each DMX output with independent driver and status indicator
- Control via RDM
- Multicolor OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Installation; stage; theater; rental
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397735536

Weight: 2,55 kg

Length: 0.52 m

Width: 0.23 m

Height: 0.10 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	5 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	1.45 m

Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
DMX input:	2 x 3-pin XLR (M) mounting version
DMX output:	8 x 3-pin XLR (F) mounting version separate (galvanic) with independent driver and status indicator
Control:	RDM
Housing color:	Black
Attachment system:	M10 thread
Display type:	Multicolor OLED display
Use of brands:	Built with SEETRONIC connector
Material:	Metal
Housing design:	(19") 48.3 cm rack installation 1 U
Mounting depth:	23 cm
Dimensions:	Width: 48.3 cm Depth: 16 cm Height: 4.4 cm
Weight:	2.23 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x device
1 x power cord
1 x user manual