

## OMNITRONIC MPVZ-350.6 PA Mixing Amplifier

6 zone PA mixing amplifier adjustable zones, 350 W RMS

Art. No.: 80709791

GTIN: 4026397422184



### Features:

- Comfortable control of PA speakers via 6-zone technology
- 6 PA zone outputs with separate 5-step level controls
- Output for low-impedance speakers (4-16 ohms)
- 2 rear microphone inputs (6.3 mm jack, unbal.)
- 1 front microphone input (combination XLR/6.3 mm jack, unbal.) with adjustable priority circuit
- All microphone inputs with separate level controls
- 3 line inputs (stereo RCA) with separate level controls
- 1 line output (stereo RCA)
- Chime, switchable
- Treble and bass control for the output signal
- 7-digit LED level meter
- Master control for the output signal
- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

### Logistic

EAN / GTIN: 4026397422184

Weight: 14,30 kg

Length: 0.53 m

Width: 0.49 m

Height: 0.18 m

### Technical specifications:

|                    |                                          |
|--------------------|------------------------------------------|
| Power supply:      | 230 V AC, 50 Hz                          |
| Power consumption: | 700.00 W                                 |
| Output power:      | 350 W RMS                                |
| Power connection:  | Fixed power supply cord with safety plug |

|                   |                                                                                                                                                                                                                                                              |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency range:  | 80 - 16000 Hz                                                                                                                                                                                                                                                |
| S/N ratio:        | >75 dB microphone<br>>85 dB line                                                                                                                                                                                                                             |
| THD:              | <0.5 % at 1 kHz                                                                                                                                                                                                                                              |
| Cooling:          | 1 x temperature-controlled fan , air flow from front to rear                                                                                                                                                                                                 |
| Impedance:        | Public address systems 100V; 4-16 ohms; Public address systems 70V                                                                                                                                                                                           |
| Zone output:      | 6 adjustable zones                                                                                                                                                                                                                                           |
| Circuitry:        | Class AB                                                                                                                                                                                                                                                     |
| Control elements: | Power switch                                                                                                                                                                                                                                                 |
| Controls:         | Current limiting; short-circuit; power on/off transient; power on/off transient; Overvoltage; short-circuit                                                                                                                                                  |
| Status LED:       | Power, fault, level meter                                                                                                                                                                                                                                    |
| Connections:      | Input: microphone via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Input: microphone via 2 x 6.3 mm plug (unbal.)<br>Input: line via 3 x stereo RCA 0.3 V<br>Output: rec. via 1 x stereo RCA<br>Output: speaker via screw terminal |
| Equalizer:        | Master: 1 x 2-band tone control mono                                                                                                                                                                                                                         |
| Material:         | Metal                                                                                                                                                                                                                                                        |
| Color:            | Black                                                                                                                                                                                                                                                        |
| Housing design:   | (19") 48.3 cm rack installation 2 U                                                                                                                                                                                                                          |
| Dimensions:       | Width: 48.3 cm<br>Depth: 38.5 cm<br>Height: 8.9 cm                                                                                                                                                                                                           |
| Weight:           | 12.80 kg                                                                                                                                                                                                                                                     |

### Scope of delivery:

1 x amplifier  
1 x user manual