

OMNITRONIC PAA-360 PA Amplifier

PA power amplifier, 360 W RMS

Art. No.: 80709811

GTIN: 4026397703702



List price: 474.81 €

incl. 19% VAT.

Features:

- 1 line input (XLR and 6.3 mm jack)
- 1 feed-through output (optionally XLR or 6.3 mm jack)
- Master control
- LED indicators for power, level, clip and fault
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Package contents

- 1 x amplifier, 1 x user manual, 2 x holder, 4 x screw

Logistic

EAN / GTIN: 4026397703702

Weight: 8,20 kg

Length: 0.53 m

Width: 0.45 m

Height: 0.18 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	720 W
Output power:	360 W RMS
Power connection:	Fixed power supply cord with safety plug
Frequency range:	80 - 16000 Hz
S/N ratio:	>90 dB
THD:	<0,5 % at 1 kHz
Impedance:	4-16 ohms; public address systems 100V; Public address systems 70V
Circuitry:	Class AB

Controls:	Softstart; overheat; overload; short-circuit; DC voltage
Status LED:	Level meter, power, fault, clip
Connections:	Input: line via 1 x 6.3 mm jack socket (mono) mounting version Input: line via 1 x 3-pin XLR 0,8 V Output: line via 1 x 6.3 mm jack socket (mono) mounting version Output: line via 1 x 3-pin XLR
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 38,5 cm Height: 9,2 cm
Weight:	6,80 kg