

HONEYWELL Projector Speaker L-VBM20A/EN IP65(EN54)  
Bidirectional projector speaker

Art. No.: 80710008  
GTIN: 4026397518993



The article is no longer in our assortment.

Features:

- EN 54-16 certified and EN 60849 compliant
- 2-way coaxial system with 2 x 13 cm woofer (5.25")
- 100 V transformer with 4 power taps
- Intelligible voice and superior sound reproduction
- White grille RAL9003
- Swivel bracket for ceiling or wall mounting
- Indoor and outdoor use (IP65)
- EASE data available in the download section
- Complies with EN 54-24
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397518993  
Weight: 3,45 kg  
Length: 0.27 m  
Width: 0.19 m  
Heigh: 0.19 m

Technical specifications:

|                    |                                   |
|--------------------|-----------------------------------|
| IP classification: | IP65                              |
| Power connection:  | Fixed supply cord with open wires |
| Power:             | Program: 30W<br>Rated: 20W RMS    |
| Frequency range:   | 150 - 20000 Hz                    |
| Max. SPL:          | 92 dB                             |
| Impedance:         | Public address systems 100V       |
| Standard:          | EN 54-24,                         |

|                  |                                                               |
|------------------|---------------------------------------------------------------|
| Power tapping:   | 2,5W; 5W; 10W; 20W RMS via no connector/cable only switchable |
| Speaker:         | 1 x woofer 5"                                                 |
| Type of speaker: | Projector speaker                                             |
| Dimensions:      | Width: 14 cm<br>Depth: 19,5 cm<br>Height: 14 cm               |
| Weight:          | 3,20 kg                                                       |