

OMNITRONIC PS-30S Projector Speaker

Weather-proof 5" speaker (IP44) with mount, public address systems 100V, 30 W RMS

Art. No.: 80710374

GTIN: 4026397523089



Features:

- 4-step power selector
- Durable plastic cabinet with metal grille
- With mounting bracket
- Suitable for outdoor use IP44
- For application areas such as: Installation

Logistic

EAN / GTIN: 4026397523089
Weight: 2,20 kg
Length: 0.26 m
Width: 0.24 m
Heigh: 0.21 m

Technical specifications:

IP classification:	IP44
Power:	Program: 60W Rated: 30W RMS (100V PA) Rated: 30W RMS (8 ohms)
Frequency range:	150 - 15000 Hz
Sensitivity:	96 dB
Max. SPL:	114 dB
Impedance:	Public address systems 100V; 8 ohms
Housing color:	Grey
Attachment system:	1x Mounting bracket

Power tapping:	3.75W; 7.5W; 15W; 30W RMS via selector switch switchable
Speaker:	1 x full range loudspeaker 5" with ferrit magnet Basket material: steel Conematerial: weatherproof Cardboard/paper
Type of speaker:	Projector speaker
Material:	Plastic
Dimensions:	Depth: 23.5 cm Diameter: Ø 18 cm
Weight:	1.85 kg

Scope of delivery:
1 x speaker
1 x user manual