



Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (average lifetime 2000 h)
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397340723

Weight: 0,03 kg

Length: 0.04 m

Width: 0.04 m

Heigh: 0.06 m

Technical specifications:

| | |
|---------------------|--------------|
| Voltage (lamps): | 24 V, AC |
| Nominal wattage: | 50 W |
| Base: | GX5.3 |
| Lamp type: | Halogen lamp |
| Lamp specification: | Dimmable |

Hot restrike

| | |
|------------------------------------|--------------------------|
| Beam angle: | 12° |
| Color of light: | White |
| Color temperature: | 2500K |
| Color rendering index (CRI): | 95 Ra |
| Lead time: | 0 s |
| Construction: | MR-16; reflector; bi pin |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 2000 h |
| Dimensions (LxD): | 81x51 mm |
| Weight: | 0.02 kg |
| Energy efficiency class (A++ - E): | D |

Scope of delivery:
