

## OMNILUX MR-16 24V/50W GX-5.3 SP 38° EYC

Cool-beam mirrored lamp

Art. No.: 91205817

GTIN: 4026397343496



**The article is no longer in our assortment.**

### Features:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long life
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

### Logistic

EAN / GTIN: 4026397343496

Weight: 0,03 kg

Length: 0.04 m

Width: 0.04 m

Heigh: 0.06 m

### Technical specifications:

|                  |                                                                                          |
|------------------|------------------------------------------------------------------------------------------|
| Voltage (lamps): | 24 V, AC                                                                                 |
| Nominal wattage: | 50 W                                                                                     |
| Base:            | GX5.3                                                                                    |
| Lamp type:       | Halogen lamp; clear lamp; low voltage lamp; reflector lamp; halogen bulb; cool Beam lamp |

|                                    |                          |
|------------------------------------|--------------------------|
| Lamp specification:                | Dimmable<br>Hot restrike |
| Beam angle:                        | 38°                      |
| Color of light:                    | White                    |
| Color temperature:                 | 2500K                    |
| Color rendering index (CRI):       | 95 Ra                    |
| Lead time:                         | 0 s                      |
| Construction:                      | MR-16; reflector; bi pin |
| Operating temperature max.:        | 40° C                    |
| Operating temperature min.:        | 20° C                    |
| Burning position:                  | S180 (universal)         |
| Lamp life:                         | 2000 h                   |
| Dimensions (LxD):                  | 81x51 mm                 |
| Weight:                            | 0,02 kg                  |
| Energy efficiency class (A++ - E): | D                        |